

MOSO[®] Zebra Veneer

Product

MOSO Zebra veneer is sliced from bamboo blocks, in which both natural and caramel bamboo strips have been placed. Because of the obvious similarity with a zebra, this pattern is called ZEBRA. To avoid cracks during handling the veneer is backed with a thin, but strong cellulose fleece, which enable easy pressing of the veneer sheets on a carrier panel.



Product Line

Color	Style	Thickness(mm)	Dimensions (mm)
1 strip Natural + 1 strip Caramel	Side pressed	0.6	2500x430
2 strips Natural + 1 strip Caramel	Side pressed	0.6	2500x430
2 strips Caramel + 1 strip Natural	Side pressed	0.6	2500x430
3 strips Natural + 2 strips Caramel	Side pressed	0.6	2500x430

Application

MOSO Zebra veneer can be pressed on other carrier materials (chipboard, multiplex or MDF), used for furniture, cabinets, doors, etc. The backing is a cellulose fleece which is bonded with D3 water-resistant PVAC glue. The cellulose backing can endure shortly temperatures above 220 degree Celsius. When pressed under high pressure and high temperature a considerable cooling time should be taken into account before stacking the cooled (max. 60 °C) panels. To press the backed bamboo veneer MOSO advises to carry out a glue test first, to determine the exact pressing time, temperature and pressure.

Technical Characteristics

- Equilibrium MC : 10% at 20 °C and 65% Rel. Air Humidity
 8% at 20 °C and 50% Rel. Air Humidity
- Density : 700kg/m³
- Backing: Non woven cellulose fleece 30 gr / m²
 D3-waterresistant PVAC glue (50 gr / m²)
- Emission formaldehyde : < 0.124mg/m³ (E1 norm)